



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

Chemtrec: (800) 424-9300

Poison Center: (800) 562-8236

Revision Date: January 8th, 2019

SAFETY DATA SHEET

Identity: Barium Oxide

Formula: BaO

SECTION I - GENERAL INFORMATION

Manufacturer: Super Conductor Materials, Inc.

The information below is believed to be accurate and represents the best information available to Super Conductor Materials, Inc. However, SCM makes no warranty, expressed or implied with respect to such information and assumes no liability resulting from its use.

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Molecular weight: 153.33

CAS #	OSHA PEL	ACGIH TLV	%
1304-28-5	0.5 mg/m ³	0.5 mg/m ³	0.0 -100.0 %

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

Physical States: Solid

Boiling Point: 2000.00 °C

Vapor Pressure (vs. air or mmHg): N/A

Melting Point: 1923.00 °C

Density: 5.7 gm/cc

Evaporation Rate: N/A

Flash Point: N/A

Solubility in water: Soluble

Appearance and odor: White-yellowish powder and pieces; no odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA:

Method Used: Unknown

Explosive Limits: LEL: N/A

UEL: N/A

Extinguishing Media: Use suitable extinguishing agent for surrounding material and type of fire

USE: Class D or other metal extinguishing agent.

DO NOT USE: Water.

Special Fire Fighting Procedures:

Firefighters must wear full face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. Fumes from fire are hazardous. Isolate runoff to prevent environmental pollution.



Flammable Properties and Hazards:

- Barium oxide combustible by spontaneous chemical reaction.
- Produces heat on contact with water and moisture.
- Is very alkaline.
- Absorbs moisture and carbon dioxide on exposure to air.
- On contact with water or steam it reacts violently to form barium hydroxide with the evolution of heat.

SECTION V - REACTIVITY DATA

Stability: Unstable.

Conditions to Avoid (instability): Water, moisture and air.

Incompatibility: Water, acids, H₂S, hydroxylamine, N₂O₄, triuranium octaoxide, SO₃.

Hazardous Decomposition or Byproducts: Barium oxide and barium hydroxide.

Hazardous Polymerization: Will not occur.

Conditions to avoid (hazardous polymerization): None.

SECTION VI - HEALTH HAZARD DATA

Route of Entry: Inhalation? Yes Ingestion? Yes Skin? Yes Eyes? Yes

The soluble barium salts, such as the chloride and sulfide are poisonous when ingested. Few cases of industrial systemic poisoning have been reported, but one investigator describes a fatal case of poisoning attributed to barium oxide, the symptoms being severe abdominal pain with vomiting, dyspnea, rapid pulse paralysis of the arm and leg and eventually cyanosis and death. (Sax, Dangerous Properties of Industrial Materials, eighth edition)

Signs and Symptoms of Overexposure:

Inhalation: May cause redness, inflammation and possible chemical burns. Acute poisoning may cause irritation of the nose and eyes, muscular twitching, fatigue, abdominal cramps, cold sweat, slow heart rate and death from heart stopping.

Ingestion: May cause chemical burns. Acute barium poisoning may cause: a slow, hard pulse and elevated blood pressure; excessive salivation; vomiting; colic; violent diarrhea; convulsive tremors; muscular paralysis and paralysis of the central nervous system; strong vasoconstriction, due to the direct barium stimulation of arterial muscles, raises blood pressure. High blood pressure can cause the stomach, intestines and kidneys to hemorrhage. Chronic barium poisoning is similar but less severe than acute barium poisoning.

Skin: May cause redness, itching, inflammation and chemical burns.

Eye: May cause redness, itching, inflammation, chemical burns and watering.

Health Hazards (Acute and Chronic):

Inhalation:

Acute: Chemical burns as it reacts with moisture on living tissue. May cause acute poisoning with progressive symptoms.



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

Chronic: Not applicable.

Ingestion:

Acute: DANGER-POISON. Chemical burns as it may react with moisture on living tissue. May cause poisoning, vomiting, colic, diarrhea, slow irregular pulse, transient hypertension, convulsions, tremors, muscular paralysis, and acute barium poisoning.

Chronic: May cause chronic barium poisoning.

Skin:

Acute: Chemical burns as it reacts with moisture on living tissue.

Chronic: May cause dermatitis.

Eye:

Acute: Chemical burns as it reacts with moisture on living tissue.

Chronic: May cause corneal opacity and blindness.

Target Organs: May affect upper respiratory system, central nervous system, heart, skin and eyes.

Carcinogenicity: NTP? Yes IARC Monographs? Yes OSHA Regulated? Yes

Medical Conditions Aggravated by Exposure: Pre-existing respiratory, gastric and skin disorders.

Emergency and First Aid Procedures:

Inhalation: Remove victim to fresh air, keep warm and quiet, and give oxygen if breathing is difficult; seek medical attention

Ingestion: Give 1-2 glasses of milk or water and induce vomiting, seek medical attention. Never induce vomiting or give anything by mouth to an unconscious person

Skin: Remove contaminated clothing, brush material off skin, wash affected area with mild soap and water, and seek medical attention if symptoms persist

Eye: Flush eyes with lukewarm water, lifting upper and lower eyelids for at least 15 minutes and seek medical attention

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in case material is released or spilled:

Wear appropriate respiratory and protective equipment specified in section VIII. Isolate spill area, provide ventilation and extinguish sources of ignition. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for proper disposal. Take care not to raise dust.

Waste disposal method:

Dispose of in accordance with state, local, and federal regulations.

Hazard Label Information:

Store in cool, dry area and in tightly sealed container. Wash thoroughly after handling.

SECTION VIII - CONTROL MEASURES

Protective Equipment Summary (Hazard Label Information):

NIOSH approved respirator, impervious gloves, safety glasses, clothes to prevent contact.



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

Ventilation:

Local Exhaust: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Special: Handle in a controlled atmosphere

Mechanical (General): Not recommended

Other: Handle in an inert gas such as argon

Work/Hygienic/Maintenance Practices:

Implement engineering and work practice controls to reduce and maintain concentration of exposure at low levels. Use good housekeeping and sanitation practices. Do not use tobacco or food in work area. Wash thoroughly before eating or smoking. Do not blow dust off clothing or skin with compressed air.

Please be advised that N/A can either mean Not Applicable or No Data Has Been Established
