

Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

Chemtrec: (800) 424-9300 Poison Center: (800) 562-8236 Revision Date: January 8th, 2019

SAFETY DATA SHEET

Identity: Graphite (ATJ) Formula: C
SECTION I - GENERAL INFORMATION

Manufacturer: Super Conductor Materials, Inc.

The information below is believed to be accurate and represents the best information available to Super Conductor Materials, Inc. However, SCM makes no warranty, expressed or implied with respect to such information and assumes no liability resulting from its use.

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Molecular weight: 12.01

<u>CAS # OSHA PEL ACGIH TLV %</u> 7782-42-5 15mg/m3 2mg/m3 0.0-100.0%

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Physical States: Solid

Boiling Point: N/A Vapor Pressure (vs. air or mmHg): N/A Melting Point: $3652.00 \,^{\circ}\text{C} - 3697.00 \,^{\circ}\text{C}$ Specific Gravity(H₂O=1): 2.25g/cm^3

Evaporation Rate: N/A Flash Point: N/A

Solubility in water: Insoluble

Appearance and odor: Black powder and pieces, no odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA:

Method Used: N/A Explosive Limits: LEL: N/A UEL: N/A

Extinguishing Media: Use suitable extinguishing agent for surrounding materials and type of fire.

Special Fire Fighting Procedures:

Firefighters must wear full face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. Fumes from fire are hazardous. Isolate runoff to prevent environmental pollution.

Unusual Fire and Explosion Hazards:

When heated to decomposition, graphite may emit carbon dioxide and carbon monoxide.



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

SECTION V - REACTIVITY DATA

Stability: Stable

Conditions to Avoid (instability): None

Incompatibility: Chlorine trifluoride, fluorine, potassium, potassium superoxide.

Hazardous Decomposition or Byproducts: Carbon dioxide and carbon monoxide.

Hazardous Polymerization: Will not occur.

Conditions to avoid (hazardous polymerization): None.

SECTION VI - HEALTH HAZARD DATA

Route of entry: Inhalation? Yes Ingestion? Yes

Eyes? Yes Skin? Yes

Other? No

To the best of our knowledge the chemical, physical and toxicological properties of graphite have not been thoroughly investigated and recorded.

Signs and Symptoms of Overexposure:

Inhalation: May cause a red, dry, throat and coughing. *Ingestion:* No acute or chronic health effects recorded.

Skin: May cause redness and itching.

Eye: May cause redness, itching and watering.

Health Hazards (Acute and Chronic):

Inhalation:

Acute: Inhalation of dust or powder may cause irritation to the respiratory system.

Chronic: Inhalation of finely divided powder may cause pulmonary fibrosis, emphysema and

corpulmonate.

Ingestion:

Acute: No acute health effects recorded. Chronic: No chronic health effects recorded.

Skin:

Acute: May cause mild irritation.

Chronic: No chronic health effects recorded.

Eye:

Acute: Dust and powder may cause mild irritation.

Chronic: No chronic health effects recorded.

Target Organs: No target organs recorded.

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No Medical Conditions Aggravated by Exposure: Pre-existing asthma and emphysema conditions.



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

Emergency and First Aid Procedures:

Inhalation: Remove victim to fresh air, keep warm and quiet, and give oxygen if breathing is

difficult; seek medical attention

Ingestion: Give 1-2 glasses of milk or water and induce vomiting, seek medical attention. Never

induce vomiting or give anything by mouth to an unconscious person

Skin: Remove contaminated clothing, brush material off skin, wash affected area with mild

soap and water, and seek medical attention if symptoms persist

Eye: Flush eyes with lukewarm water, lifting upper and lower eyelids for at least 15 minutes

and seek medical attention

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in case material is released or spilled:

Wear appropriate respiratory and protective equipment specified in section VIII. Isolate spill area, provide ventilation and extinguish sources of ignition. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for proper disposal. Take care not to raise dust.

Waste disposal method:

Dispose of in accordance with state, local, and federal regulations.

Hazard Label Information:

Store in cool, dry area and in tightly sealed container. Wash thoroughly after handling.

SECTION VIII - CONTROL MEASURES

Protective Equipment Summary (Hazard Label Information):

NIOSH approved respirator, impervious gloves, safety glasses, clothes to prevent contact.

Ventilation:

Local Exhaust: To maintain concentration at low exposure levels.

Mechanical (General): Recommended.

Work/Hygienic/Maintenance Practices:

Implement engineering and work practice controls to reduce and maintain concentration of exposure at low levels. Use good housekeeping and sanitation practices. Do not use tobacco or food in work area. Wash thoroughly before eating or smoking. Do not blow dust off clothing or skin with compressed air.

Please be advised that N/A can either mean Not Applicable or No Data Has Been Established