



Chemtec: (800) 424-9300
Poison Center: (800) 562-8236
Revision Date: January 8th, 2019

SAFETY DATA SHEET

Identity: Cerium Fluoride

Formula: CeF₃

SECTION I - GENERAL INFORMATION

Manufacturer: Super Conductor Materials, Inc.

The information below is believed to be accurate and represents the best information available to Super Conductor Materials, Inc. However, SCM makes no warranty, expressed or implied with respect to such information and assumes no liability resulting from its use.

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Molecular weight: 197.12

CAS #	OSHA PEL	ACGIH TLV	%
7758-88-5	2.5mg (F)/m ³	2.5mg (F)/m ³	0.0-100.0%

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

Physical States: Solid

Boiling Point: 2300.00°C – 2327.00°C	Vapor Pressure (vs. air or mmHg): N/A
Melting Point: 1460.00°C	Density: 6.16 g/cm ³
Evaporation Rate: N/A	Flash Point: N/A
Solubility in water: Insoluble/ Soluble in H ₂ SO ₄	

Appearance and odor: White crystalline powder and pieces, no odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA:

Method Used: Unknown *Explosive Limits:* LEL: N/A UEL: N/A

Extinguishing Media: Use suitable extinguishing media for surrounding materials and type of fire.

Special Fire Fighting Procedures:

Firefighters must wear full face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. Fumes from fire are hazardous. Isolate runoff to prevent environmental pollution.

Flammable Properties and Hazards:

When heated to decomposition or comes in contact with acids/acid fumes, cerium fluoride may emit toxic fumes of fluorine, hydrogen fluoride vapors and fluorine gas.



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

SECTION V - REACTIVITY DATA

Stability: Stable

Conditions to Avoid (instability): None

Incompatibility: Acids

Hazardous Decomposition or Byproducts: Fumes of fluorine, hydrogen fluoride, fluorine gas and cerium oxide.

Hazardous Polymerization: Will not occur

Conditions to avoid (hazardous polymerization): None

SECTION VI - HEALTH HAZARD DATA

Route of entry: Inhalation? Yes Skin? Yes Eyes? Yes Ingestion? Yes Other: N/A

To the best of our knowledge the chemical, physical and toxicological properties of cerium fluoride have not been thoroughly investigated and recorded.

Cerium is considered a rare earth metal. These metals are moderately to highly toxic. The symptoms of toxicity of the rare earth elements include writhing, ataxia, labored respiration, walking on the toes with arched back and sedation (animals). The rare earth elements exhibit low toxicity by ingestion exposure. However, the intraperitoneal route is highly toxic while the subcutaneous route is poison to moderately toxic. The production of skin and lung granulomas after exposure to them requires extensive protection to prevent such exposure. Inorganic fluorides are generally highly irritating and toxic. Chronic fluorine poisoning, or "fluorosis," occurs among miners of cryolite, and consists of sclerosis of the bones, caused by fixation of the calcium by fluorine. There may also be some calcification of the ligaments. The teeth are mottled, and there is osteosclerosis and ostemalacia. Large doses can cause very severe nausea, vomiting, diarrhea, aggravate attacks of asthma and severe bone changes, making normal movements painful. Some signs of pulmonary fibrosis are noted. Some enzyme system effects are reported. Irritants to the eyes, skin and mucous membranes. Loss of weight, anorexia, anemia, wasting and cachexia and dental defects are among the common findings in chronic fluorine poisoning. There may be an eosinophilia and impairment of growth in young workers. Symptoms of intoxication include gastric, intestinal, circulatory, respiratory and nervous complaints and rashes. (Sax, Dangerous Properties of Industrial Materials, eighth edition)

Signs and Symptoms of Overexposure:

Inhalation: Fibrosis may cause: sclerosis of the bones, calcification of ligaments, mottled teeth, osteosclerosis, ostemalacia, loss of weight, anorexia, anemia, wasting, cachia and dental defects.

Ingestion: May cause nausea, vomiting, diarrhea, abdominal burning and cramp-like pain.

Skin: May cause redness, itching and burning.

Eye: May cause redness, itching, burning and watering.

Health Hazards (Acute and Chronic):

Inhalation:

Acute: May cause irritation to the respiratory tract and mucous membrane. Dusts may cause asthma attacks and lung damage such as lung granulomas and pulmonary edema. Large doses may cause immediate defecation, writhing, loss of muscle coordination, labored respiration, sedation, hypotension,



391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com
dyspnea, hyperemia, liver edema and necrosis, portal congestion, pleural effusion and granulomatous peritonitis with serous and hemorrhagic ascites, respiratory and cardiac failure.

Chronic: May cause fluorosis, pulmonary fibrosis, severe bone changes, hyperemia, cellular eosinophilia and vascular granulomata, acute chemical pneumonitis, subacute bronchitis and focal hypertropic emphysema.

Ingestion:

Acute: May cause gastrointestinal irritation.

Chronic: May affect the coagulation rate of the blood, renal and hepatic functions, circulatory, enzyme and nervous system.

Skin:

Acute: May cause irritation, rashes and skin granulomas.

Chronic: May cause dermatitis, sensitivity to heat, itching and skin lesions.

Eye:

Acute: May cause irritation.

Chronic: No chronic health effects recorded.

Target Organs: May affect the skeleton, kidneys, central nervous system, respiratory system, skin.

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

Medical Conditions Aggravated by Exposure: Pre-existing respiratory disorders

Emergency and First Aid Procedures:

Inhalation: Remove victim to fresh air, keep warm and quiet, and give oxygen if breathing is difficult; seek medical attention

Ingestion: Give 1-2 glasses of milk or water and induce vomiting, seek medical attention. Never induce vomiting or give anything by mouth to an unconscious person

Skin: Remove contaminated clothing, brush material off skin, wash affected area with mild soap and water, and seek medical attention if symptoms persist

Eye: Flush eyes with lukewarm water, lifting upper and lower eyelids for at least 15 minutes and seek medical attention

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in case material is released or spilled:

Wear appropriate respiratory and protective equipment specified in section VIII. Isolate spill area, provide ventilation and extinguish sources of ignition. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for proper disposal. Take care not to raise dust.

Waste disposal method:

Dispose of in accordance with state, local, and federal regulations.

Hazard Label Information:

Store in cool, dry area and in tightly sealed container. Wash thoroughly after handling.



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

SECTION VIII - CONTROL MEASURES

Protective Equipment Summary (Hazard Label Information):

NIOSH approved respirator, impervious gloves, safety glasses, clothes to prevent contact.

Ventilation:

Local Exhaust: If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

Mechanical (General): Recommended.

Work/Hygienic/Maintenance Practices:

Implement engineering and work practice controls to reduce and maintain concentration of exposure at low levels. Use good housekeeping and sanitation practices. Do not use tobacco or food in work area. Wash thoroughly before eating or smoking. Do not blow dust off clothing or skin with compressed air.

Please be advised that N/A can either mean Not Applicable or No Data Has Been Established