



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

Chemtrec: (800) 424-9300
Poison Center: (800) 562-8236
Revision Date: January 8th, 2019

SAFETY DATA SHEET

Identity: Chromium

Formula: Cr

Section I - General Information

Manufacturer: Super Conductor Materials, Inc.

The information below is believed to be accurate and represents the best information available to Super Conductor Materials, Inc. However, SCM makes no warranty, expressed or implied with respect to such information and assumes no liability resulting from its use.

Section II - Hazardous Ingredients/Identity Information

Molecular weight: 51.99

CAS #	OSHA PEL	ACGIH TLV	%
7440-47-3	1.0 mg/m ³	0.5 mg/m ³	0.0-100.0%

Section III - Physical/Chemical Characteristics

Physical States: Solid

Boiling Point: 2671.00°C

Specific Gravity (water=1): 7.19 at 18.0°C

Melting Point: 1907.00°C

Vapor Pressure: 1mm Hg at 1616°C

Solubility in water: Insoluble

Flash Point: NA

Auto ignition Temp: 400°C

Appearance and odor: Steel gray metallic pieces or powder; no odor.

Section IV - Fire and Explosion Hazard Data:

Method used: N/A

Extinguishing Media: AUTOIGNITION TEMPERATURE: 1890 C for pieces. Use suitable extinguishing agent for surrounding materials and type of fire.

Special Fire Fighting Procedures:

Firefighters must wear full face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. Fumes from fire are hazardous. Isolate runoff to prevent environmental pollution.

Unusual Fire and Explosion Hazards:

Ignites and is potentially explosive in atmospheres of carbon dioxide. Chromium reacts violently or explosively when heated with ammonium nitrate and bromine pentafluoride. Chromium has an incandescent reaction with nitrogen oxide or sulfur dioxide. Powders prepared by evaporation of mercury from chromium amalgam may be pyrophoric.



Section V - Reactivity Data

Stability: Stable

Conditions to Avoid: None.

Incompatibility: Strong oxidizing agents, ammonium nitrite, bromine pentafluoride and carbon dioxide

Hazardous Decomposition or Byproducts: Chromium oxide fumes

Hazardous Polymerization: Will not occur

Conditions to avoid (hazardous polymerization): none

Section VI - Health Hazard Data

Route of entry: Inhalation? Yes Skin? No Eyes? No Ingestion? Yes Other: N/A

Chromium: Confirmed human carcinogen with experimental tumorigenic data. Human poison by ingestion with gastrointestinal effects. (Sax, Dangerous Properties of Industrial Materials)

Signs and Symptoms of Overexposure:

Inhalation: May cause a red, dry throat, coughing and shortness of breath;

Ingestion: May cause gastritis, convulsions, asphyxia, giddiness, nausea, diarrhea and vomiting

Skin: May cause redness and itching

Eye: May cause redness, itching, and watering

Health Hazards (Acute and Chronic):

Inhalation:

Acute: May cause a red, dry throat.

Chronic: May cause histologic fibrosis of lungs, nasal and/or lung cancer.

Ingestion:

Acute: May cause gastrointestinal disorders.

Chronic: No chronic health effects recorded.

Skin:

Acute: May cause abrasive irritation.

Chronic: No chronic health effects recorded.

Eye:

Acute: May cause abrasive irritation.

Chronic: No chronic health effects recorded.

Target Organs: May affect the Respiratory system

Carcinogenicity: NTP? Yes

IARC Monographs? No

OSHA Regulated? No

Medical Conditions Aggravated by Exposure: Pre-existing respiratory disorders, pulmonary functions and asthma

Emergency and First Aid Procedures:

Inhalation: Remove victim to fresh air, keep warm and quiet, and give oxygen if breathing is difficult; seek medical attention

Ingestion: Give 1-2 glasses of milk or water and induce vomiting, seek medical attention. Never induce vomiting or give anything by mouth to an unconscious person

Skin: Remove contaminated clothing, brush material off skin, wash affected area with mild soap and water, and seek medical attention if symptoms persist

Eye: Flush eyes with lukewarm water, lifting upper and lower eyelids for at least 15 minutes and seek medical attention



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

Section VII - Precautions for Safe Handling and Use

Steps to be taken in case material is released or spilled:

Wear appropriate respiratory and protective equipment specified in section VIII. Isolate spill area, provide ventilation and extinguish sources of ignition. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for proper disposal. Take care not to raise dust. Use non-sparking tools.

Waste disposal method:

Dispose of in accordance with state, local, and federal regulations.

Hazard Label Information:

Store in cool, dry area and in tightly sealed container. Wash thoroughly after handling.

Section VIII - Control Measures

Protective Equipment Summary (Hazard Label Information):

NIOSH approved respirator, impervious rubber gloves, safety glasses, clothes to prevent skin contact.

Ventilation:

Local Exhaust: May be necessary to control any air contaminants to within their PELs or TLVs during the use of this product

Mechanical (General): Good ventilation is recommended

Work/Hygienic/Maintenance Practices:

Implement engineering and work practice controls to reduce and maintain concentration of exposure at low levels. Use good housekeeping and sanitation practices. Do not use tobacco or food in work area. Wash thoroughly before eating or smoking. Do not blow dust off clothing or skin with compressed air.

Please be advised that N/A can either mean Not Applicable or No Data Has Been Established