

Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · www.scm-inc.com

Chemtrec: (800) 424-9300 Poison Center: (800) 562-8236

Revision Date: January 8th, 2019

SAFETY DATA SHEET

Identity: Lanthanum Aluminate Oxide Formula: LaAlO3

SECTION I - GENERAL INFORMATION

Manufacturer: Super Conductor Materials, Inc.

The information below is believed to be accurate and represents the best information available to Super Conductor Materials, Inc. However, SCM makes no warranty, expressed or implied with respect to such information and assumes no liability resulting from its use.

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Molecular weight: 213.88

CAS# OSHA PEL ACGIH TLV 12003-65-5 10mg (A1)/m3 100.0% 10mg (A1)/m3

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

Physical States: Solid

Vapor Pressure (vs. air or mmHg): N/A Boiling Point: N/A Melting Point: 2,080°C (3,776°F) Specific Gravity (Water=1): N/A

Evaporation Rate: N/A Flash Point: N/A

Solubility in water: Insoluble

Appearance and odor: Tan powder and pieces, no odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA:

Method Used: Unknown Explosive Limits: LEL: N/A Extinguishing Media: Use suitable extinguishing agent for surrounding material and type of fire

Special Fire Fighting Procedures:

Firefighters must wear full face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. Fumes from fire are hazardous. Isolate runoff to prevent environmental pollution.

Unusual Fire and Explosion Hazards: None determined

SECTION V - REACTIVITY DATA

Stability: Stable

Conditions to Avoid (instability): N/A



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · www.scm-inc.com *Incompatibility (Materials to avoid):* Strong oxidizing agents

Hazardous Decomposition or Byproducts: Hazardous Polymerization: Will not occur

Conditions to avoid (hazardous polymerization): N/A

SECTION VI - HEALTH HAZARD DATA

Routes of entry: Inhalation? Yes Skin? Yes Eyes? Yes Ingestion? Yes Other? No

To the best of our knowledge the chemical, physical and toxicological properties of lanthanum aluminate have not been thoroughly investigated and recorded.

Lanthanum is considered a rare earth metal. These metals are moderately to highly toxic. The symptoms of toxicity of the rare earth elements include writhing, ataxia, labored respiration, walking on the toes with arched back and sedation. The rare earth elements exhibit low toxicity by ingestion exposure. However, the intraperitoneal route is highly toxic while the subcutaneous route is poison to moderately toxic. The production of skin and lung granulomas after exposure to them requires extensive protection to prevent such exposure. (Sax, Dangerous Properties of Industrial Materials, eighth edition)

Aluminum compounds have many commercial uses and are commonly found in industry. Inhalation of fine aluminum oxide particles is associated with Shaver's disease. (Sax, Dangerous Properties of Industrial Materials, eighth edition)

Signs and Symptoms of Overexposure:

Inhalation: May cause writhing, ataxia, labored respiration, walking on the toes with arched back and sedation

Ingestion: May cause nausea, vomiting, diarrhea, abdominal burning and cramp like pain

Skin: May cause redness, itching, and burning

Eye: May cause redness, itching, burning and watering

Health Hazards (Acute and Chronic):

Inhalation:

Acute: May cause irritation to the respiratory tract and mucous membrane. Dusts may cause lung damage such as lung granulomas and pulmonary fibrosis. Large doses may cause writhing, loss of muscle coordination, labored respiration, sedation, hypotension and cardiovascular collapse.

Chronic: Prolonged or repeated inhalation may cause writhing, loss of muscle coordination, labored respiration, sedation, hypotension and cardiovascular collapse.

Ingestion:

Acute: May cause gastrointestinal irritation and nevous afflications

Chronic: May affect the coagulation rate of the blood

Skin:

Acute: May cause irritation, rashes, lesions, and skin granulomas

Chronic: May cause dermatitis

Eye:

Acute: May cause irritation

Chronic: No chronic health effects recorded



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · www.scm-inc.com

Target Organs: May effect the respiratory system, blood and skin

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

Medical Conditions Aggravated by Exposure: Pre-existing respiratory disorder

Emergency and First Aid Procedures:

Inhalation: Remove victim to fresh air, keep warm and quiet, and give oxygen if breathing is

difficult; seek medical attention

Ingestion: Give 1-2 glasses of milk or water and induce vomiting, seek medical attention. Never

induce vomiting or give anything by mouth to an unconscious person

Skin: Remove contaminated clothing, brush material off skin, wash affected area with mild

soap and water, and seek medical attention if symptoms persist

Eye: Flush eyes with lukewarm water, lifting upper and lower eyelids for at least 15 minutes

and seek medical attention

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in case material is released or spilled:

Wear appropriate respiratory and protective equipment specified in section VIII. Isolate spill area, provide ventilation and extinguish sources of ignition. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for proper disposal. Take care not to raise dust.

Waste disposal method:

Dispose of in accordance with state, local, and federal regulations.

Hazard Label Information:

Store in cool, dry area and in tightly sealed container. Wash thoroughly after handling.

SECTION VIII - CONTROL MEASURES

Protective Equipment Summary (Hazard Label Information):

NIOSH approved respirator, impervious gloves, safety glasses, clothes to prevent contact.

Ventilation:

Local Exhaust: To maintain concentration at or below the PEL, TLV

Mechanical (General): Not recommended

Work/Hygienic/Maintenance Practices:

Implement engineering and work practice controls to reduce and maintain concentration of exposure at low levels. Use good housekeeping and sanitation practices. Do not use tobacco or food in work area. Wash thoroughly before eating or smoking. Do not blow dust off clothing or skin with compressed air.

Please be advised that N/A can either mean Not Applicable or No Data Has Been Established