



# Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

Chemtrec: (800) 424-9300  
Poison Center: (800) 562-8236  
Revision Date: January 8<sup>th</sup>, 2019

## SAFETY DATA SHEET

Identity: Lithium Carbonate

Formula: Li<sub>2</sub>CO<sub>3</sub>

### SECTION I - GENERAL INFORMATION

Manufacturer: Super Conductor Materials, Inc.

The information below is believed to be accurate and represents the best information available to Super Conductor Materials, Inc. However, SCM makes no warranty, expressed or implied with respect to such information and assumes no liability resulting from its use.

### SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Molecular weight: 73.90

CAS #	OSHA PEL	ACGIH TLV	%
554-13-2	N/A	N/A	0.0-100.0%

### SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

Physical States: Solid

Boiling Point: 1310.00°C

Vapor Pressure (vs. air or mmHg): N/A

Melting Point: 723.00°C

Specific Gravity (water = 1): 2.11gm/cc at 17.5°C

Evaporation Rate: N/A

Flash Point: N/A

Solubility in water: Slightly soluble

*Appearance and odor:* White, light alkaline powder and pieces, no odor

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA:

*Method Used:* Non-flammable

*Explosive Limits:* LEL: N/A

UEL: N/A

*Extinguishing Media:* Use suitable extinguishing agent for surrounding material and type of fire

#### *Special Fire Fighting Procedures:*

Firefighters must wear full face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. Fumes from fire are hazardous. Isolate runoff to prevent environmental pollution.

#### *Unusual Fire and Explosion Hazards:*

When heated to decomposition, lithium carbonate may emit toxic fumes



SECTION V - REACTIVITY DATA

*Stability:* Stable

*Conditions to Avoid (stability):* None

*Incompatibility:* Water, fluorine, and strong acids

*Hazardous Decomposition or Byproducts:* lithium oxide, carbon monoxide, and carbon dioxide

*Hazardous Polymerization:* Will not occur

*Conditions to avoid (hazardous polymerization):* None

SECTION VI - HEALTH HAZARD DATA

Routes of entry: Inhalation? Yes      Skin? Yes      Eyes? Yes      Ingestion? Yes      Other? No

The toxicity of lithium compounds is a function of their solubility in water. Lithium ion has central nervous system toxicity. The initial effects of lithium exposure are tremors of the hands, nausea, micturition, slurred speech, sluggishness, sleepiness, vertigo, thirst, and increased urine volume. Effects from continued exposure are apathy, anorexia, fatigue, lethargy, muscular weakness, and changes in ECG. Long-term exposure leads to hypothyroidism, leukocytosis, edema, weight gain, polydipsia/polyuria (increased water intake leading to increased urinary output), memory impairment, seizures, kidney damage, shock, hypotension, cardiac arrhythmias, coma, death. (Sax, Dangerous Properties of Industrial Materials, eighth edition).

Signs and Symptoms of Overexposure:

*Inhalation:* May cause red, dry, burning throat, inflammation and pain throughout the respiratory tract

*Ingestion:* May cause burns to the esophagus, nausea, muscular twitches and mental confusion. Human systemic effect may cause: toxic psychosis, tremors, and changes in fluid intake, muscle weakness, increased urine volume, nausea or vomiting, allergic dermatitis. Human reproductive effects may cause: on newborn including Apgar score changes and other neonatal measure or effects. Human teratogenic effects: develop mental abnormalities of the cardiovascular system, central nervous system, musculoskeletal and gastrointestinal systems.

*Skin:* May cause redness, itching, chemical burns and/or blistering

*Eye:* May cause redness, itching, watering, inflammation and/or chemical burns

Health Hazards (Acute and Chronic):

*Inhalation:*

Acute: May cause irritation to the respiratory tract and mucous membranes

Chronic: May cause pulmonary edema and lung damage

*Ingestion:*

Acute: Moderately toxic by ingestion. May cause systemic, reproductive, and teratogenic effects, circulatory failure, and cardiovascular collapse

Chronic: May cause gastrointestinal irritation, renal dysfunction, derangement of neuromuscular activity, diabetes and kidney damage

*Skin:*

Acute: May cause irritation

Chronic: None chronic health effects recorded



# Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

*Eye:*

Acute: May cause severe irritation

Chronic: None chronic health effects recorded

*Target Organs:* May affect respiratory system, skin and eyes

*Carcinogenicity:* NTP? No

IARC Monographs? No

OSHA Regulated? No

*Medical Conditions Aggravated by Exposure:* Pre-existing respiratory and skin disorders

*Emergency and First Aid Procedures:*

*Inhalation:* Remove victim to fresh air, keep warm and quiet, and give oxygen if breathing is difficult; seek medical attention

*Ingestion:* DO NOT induce vomiting, seek medical attention. Never induce vomiting or give anything by mouth to an unconscious person

*Skin:* Remove contaminated clothing, brush material off skin, wash affected area with mild soap and water, and seek medical attention if symptoms persist

*Eye:* Flush eyes with lukewarm water, lifting upper and lower eyelids for at least 15 minutes and seek medical attention

## SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

*Steps to be taken in case material is released or spilled:*

Wear appropriate respiratory and protective equipment specified in section VIII. Isolate spill area, provide ventilation and extinguish sources of ignition. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for proper disposal. Take care not to raise dust.

*Waste disposal method:* Dispose of in accordance with state, local, and federal regulations.

*Hazard Label Information:*

Store in cool, dry area and in tightly sealed container. Wash thoroughly after handling.

## SECTION VIII - CONTROL MEASURES

*Protective Equipment Summary (Hazard Label Information):*

NIOSH approved respirator, impervious rubber gloves, safety glasses, clothes to prevent contact.

*Ventilation:*

Local Exhaust: To maintain concentration at low exposure levels.

Mechanical (General): Recommended.

*Work/Hygienic/Maintenance Practices:*

Implement engineering and work practice controls to reduce and maintain concentration of exposure at low levels. Use good housekeeping and sanitation practices. Do not use tobacco or food in work area. Wash thoroughly before eating or smoking. Do not blow dust off clothing or skin with compressed air.

Please be advised that N/A can either mean Not Applicable or No Data Has Been Established