



# Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

Chemtrec: (800) 424-9300

Poison Center: (800) 562-8236

Revisions Date: January 8<sup>th</sup>, 2019

## SAFETY DATA SHEET

Identity: Magnesium Silicide

Formula: Mg<sub>2</sub>Si

### SECTION I - GENERAL INFORMATION

Manufacturer: Super Conductor Materials, Inc.

The information below is believed to be accurate and represents the best information available to Super Conductor Materials, Inc. However, SCM makes no warranty, expressed or implied with respect to such information and assumes no liability resulting from its use.

### SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Molecular weight: 76.71

CAS #	OSHA PEL	ACGIH TLV	%
22831-39-6	N/A	N/A	0.0-100.0%

### SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Physical States: Solid

Boiling Point: N/A

Vapor Pressure (vs. air or mmHg): N/A

Melting Point: 1102.00°C

Specific Gravity: 2.0 gm/cc

Evaporation Rate: N/A

Flash Point: N/A

Solubility in water: Decomposes in hot water

*Appearance and odor:* Blue powder, no odor

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA:

*Method Used:* Unknown

*Explosive Limits:* LEL: N/A

UEL: N/A

*Extinguishing Media:* Use suitable extinguishing agent for surrounding material and type of fire

#### *Special Fire Fighting Procedures:*

Firefighters must wear full face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. Fumes from fire are hazardous. Isolate runoff to prevent environmental pollution.

#### *Unusual Fire and Explosion Hazards:*

-DANGEROUS WHEN WET.

-Decomposed on heating above 500°C in water and hydrochloric acid.

-When heated to decomposition, magnesium silicide may emit toxic fumes of magnesium oxides.



SECTION V - REACTIVITY DATA

*Stability:* Stable

*Conditions to Avoid (stability):* None

*Incompatibility:* Water and hydrochloric acid

*Hazardous Decomposition or Byproducts:* Oxides of magnesium

*Hazardous Polymerization:* Will not occur

*Conditions to avoid (hazardous polymerization):* None

SECTION VI - HEALTH HAZARD DATA

*Route of Entry:* Inhalation? Yes    Ingestion? Yes    Skin? Yes    Eyes? Yes    Other? No

To the best of our knowledge the chemical, physical and toxicological properties of magnesium silicide have not been thoroughly investigated recorded.

Magnesium compounds have variable toxicity. The inhalation of fumes of freshly sublimed magnesium oxide may cause metal fume fever. There is no evidence that magnesium produces true systemic poisoning. Protection necessary for personnel handling and processing magnesium is usually no different from that which is necessary for other metals. (Sax, Dangerous Properties of Industrial Materials, eighth edition)

*Signs and Symptoms of Overexposure:*

*Inhalation:* May cause cough, mucous production, shortness of breath, nausea, muscular weakness, lethargy, hypotension, sinus irritation and cardiac arrest.

*Ingestion:* May cause gastrointestinal disturbances.

*Skin:* May cause redness, itching, and inflammation.

*Eye:* May cause redness, itching, swelling, watering and/or burning.

*Health Hazards (Acute and Chronic):*

*Inhalation:*

Acute: May cause irritation and metal fume fever

Chronic: May cause kidney damage and fibrogenic effects on the lungs

*Ingestion:*

Acute: May cause irritation

Chronic: No chronic health effects recorded

*Skin:*

Acute: May cause irritation

Chronic: No chronic effects recorded

*Eye:*

Acute: May cause severe irritation

Chronic: No chronic health effects recorded

*Target Organs:* May affect kidneys and lungs

*Carcinogenicity:* NTP? No    IARC Monographs? No    OSHA Regulated? No

*Medical Conditions Aggravated by Exposure:* Pre-existing respiratory disorders



# Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · [www.scm-inc.com](http://www.scm-inc.com)

## Emergency and First Aid Procedures:

- Inhalation:** Remove victim to fresh air, keep warm and quiet, and give oxygen if breathing is difficult; seek medical attention
- Ingestion:** Give 1-2 glasses of milk or water and induce vomiting, seek medical attention. Never induce vomiting or give anything by mouth to an unconscious person
- Skin:** Remove contaminated clothing, brush material off skin, wash affected area with mild soap and water, and seek medical attention if symptoms persist
- Eye:** Flush eyes with lukewarm water, lifting upper and lower eyelids for at least 15 minutes and seek medical attention

## SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

### *Steps to be taken in case material is released or spilled:*

Wear appropriate respiratory and protective equipment specified in section VIII. Isolate spill area, provide ventilation and extinguish sources of ignition. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for proper disposal. Take care not to raise dust.

### *Waste disposal method:*

Dispose of in accordance with state, local, and federal regulations.

### *Hazard Label Information:*

Store in cool, dry area and in tightly sealed container. Wash thoroughly after handling.

## SECTION VIII - CONTROL MEASURES

### *Protective Equipment Summary (Hazard Label Information):*

NIOSH approved respirator, impervious gloves, safety glasses, clothes to prevent contact.

### *Ventilation:*

- Local Exhaust: To maintain concentration at low exposure levels
- Special: Handle in a controlled, enclosed process
- Mechanical (General): Not recommended
- Other: Handle in an inert gas such as argon

### *Work/Hygienic/Maintenance Practices:*

Implement engineering and work practice controls to reduce and maintain concentration of exposure at low levels. Use good housekeeping and sanitation practices. Do not use tobacco or food in work area. Wash thoroughly before eating or smoking. Do not blow dust off clothing or skin with compressed air.

Please be advised that N/A can either mean Not Applicable or No Data Has Been Established