



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · www.scm-inc.com

Chemtrec: (800) 424-9300

Poison Center: (800) 562-8236

Revision Date: January 8th, 2019

SAFETY DATA SHEET

Identity: Strontium

Formula: Sr

SECTION I - GENERAL INFORMATION

Manufacturer: Super Conductor Materials, Inc.

The information below is believed to be accurate and represents the best information available to Super Conductor Materials, Inc. However, SCM makes no warranty, expressed or implied with respect to such information and assumes no liability resulting from its use.

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Molecular weight: 87.62

CAS #	OSHA PEL	ACGIH TLV	%
7440-24-6	NE	NE	0.0-100.0%

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Physical States: Solid

Boiling Point: 1382°C

Vapor Pressure (vs. air or mmHg): 13.3 hPa at 898

Melting Point: 777°C

Specific Gravity (Water=1): 2.64 g/cm³

Evaporation Rate: N/A

Flash Point: N/A

Solubility in water: Reactly violently

Appearance and odor: Silver white to pale yellow solid, no odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA:

Method Used: Unknown

Explosive Limits: LEL: N/A UEL: N/A

Extinguishing Media: Flammable solid. If involved in fire, DO NOT USE WATER, CO₂, OR HALOGENATED EXTINGUISHING AGENTS. Use dry powder extinguishing agents, dry sand or dry dolomite.

Special Fire Fighting Procedures: Firefighters must wear full face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. Fumes from fire are hazardous. Isolate runoff to prevent environmental pollution.

Unusual Fire and Explosion Hazards: Contact with water releases hydrogen (explosive).



SECTION V - REACTIVITY DATA

Stability: Stable

Conditions to Avoid (instability): Reacts with sources of moisture increasing rapidly with reduced particle size or higher.

Incompatibility (Materials to avoid): Water/ moisture, oxidizing agents, acids, O₂ (air), halogens, interhalogens.

Hazardous Decomposition or Byproducts: Hydrogen, metal oxide fume

Hazardous Polymerization: Will not occur

Conditions to avoid (hazardous polymerization): Oxidizes in air. Evolves hydrogen gas from water. Finely divided metal ignites spontaneously in air.

SECTION VI - HEALTH HAZARD DATA

Routes of entry: Inhalation? Yes Skin? Yes Eyes? Yes Ingestion? Yes Other? No

To the best of our knowledge the chemical, physical and toxicological properties of strontium have not been thoroughly investigated and reported.

Strontium has a low order of toxicity. As with calcium, the toxicity is generally a function of the anion. Acute exposure may cause excessive salivation, vomiting, colic, diarrhea, and respiratory failure in extreme cases.

Signs and Symptoms of Overexposure:

Inhalation: N/A

Ingestion: N/A

Skin: N/A

Eye: N/A

Health Hazards (Acute and Chronic):

Inhalation:

Acute: Powder or dust may cause irritation

Chronic: No chronic health effects known

Ingestion:

Acute: May cause vomiting, diarrhea and colic.

Chronic: No chronic health effects known

Skin:

Acute: May cause irritation

Chronic: May cause dermatitis

Eye:

Acute: May cause irritation

Chronic: No chronic health effects known



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · www.scm-inc.com

Target Organs: No data available

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

Medical Conditions Aggravated by Exposure: No data available

Emergency and First Aid Procedures:

Inhalation: Remove victim to fresh air, keep warm and quiet, and give oxygen if breathing is difficult; seek medical attention

Ingestion: Give 1-2 glasses of milk or water and induce vomiting, seek medical attention. Never induce vomiting or give anything by mouth to an unconscious person

Skin: Remove contaminated clothing, brush material off skin, wash affected area with mild soap and water, and seek medical attention if symptoms persist

Eye: Flush eyes with lukewarm water, lifting upper and lower eyelids for at least 15 minutes and seek medical attention

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in case material is released or spilled:

Wear appropriate respiratory and protective equipment specified in section VIII. Isolate spill area, provide ventilation and extinguish sources of ignition. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for proper disposal. Take care not to raise dust.

Waste disposal method:

Dispose of in accordance with state, local, and federal regulations.

Hazard Label Information:

Store in cool, dry area and in tightly sealed container. Wash thoroughly after handling.

SECTION VIII - CONTROL MEASURES

Protective Equipment Summary (Hazard Label Information):

NIOSH approved respirator, impervious gloves, safety glasses, clothes to prevent contact.

Ventilation:

Local Exhaust: To maintain concentration at or below the PEL, TLV

Mechanical (General): Recommended

Work/Hygienic/Maintenance Practices:

Implement engineering and work practice controls to reduce and maintain concentration of exposure at low levels. Use good housekeeping and sanitation practices. Do not use tobacco or food in work area. Wash thoroughly before eating or smoking. Do not blow dust off clothing or skin with compressed air.

Please be advised that N/A can either mean Not Applicable or No Data Has Been Established