



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

Chemtrec: (800) 424-9300
Poison Center: (800) 562-8236
Revision Date: January 8th, 2019

SAFETY DATA SHEET

Identity: Strontium zirconate

Synonyms: strontium zirconium oxide

Formula: SrZrO₃

SECTION I - GENERAL INFORMATION

Manufacturer: Super Conductor Materials, Inc.

The information below is believed to be accurate and represents the best information available to Super Conductor Materials, Inc. However, SCM makes no warranty, expressed or implied with respect to such information and assumes no liability resulting from its use.

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Molecular weight: 226.84

CAS #	OSHA PEL	ACGIH TLV	%
12036-39-4	5mg (Zr)/m ³	5mg (Zr)/m ³	0.0-100%

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

Physical States: Solid

Boiling Point: N/A

Melting Point: 2600.00°C

Evaporation Rate: N/A

Solubility in water: Insoluble

Specific Gravity (H₂O=1): 2.99gm/cc at 17.5°C

Vapor Pressure (vs. air or mmHg): 10mm at 898.0°C

Flash Point: N/A

Appearance and odor: White powder and pieces, no odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA:

Method Used: Flammable solid

Explosive Limits: LEL: N/A

UEL: N/A

Extinguishing Media:

Use suitable extinguishing agent for surrounding material and type of fire

Special Fire Fighting Procedures:

Firefighters must wear full face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. Fumes from fire are hazardous. Isolate runoff to prevent environmental pollution.

Unusual Fire and Explosion Hazards: None recorded



SECTION V - REACTIVITY DATA

Stability: Stable

Conditions to Avoid (stability): None

Incompatibility: None recorded

Hazardous Decomposition or Byproducts: None recorded

Hazardous Polymerization: Will not occur

Conditions to avoid (hazardous polymerization): None

SECTION VI - HEALTH HAZARD DATA

Routes of entry: Inhalation? Yes Skin? Yes Eyes? Yes Ingestion? Yes Other? No

To the best of our knowledge the chemical, physical and toxicological properties of strontium zirconate have not been thoroughly investigated and recorded.

Strontium compounds: The strontium ion has a low order of toxicity. It is chemically and biologically similar to calcium.

Zirconium is not an important industrial poison; however, poisoning may occur due to the excessive exposure to zirconium salts. Most zirconium compounds in common use are insoluble and considered inert. (Sax, Dangerous Properties of Industrial Materials, eighth edition)

Signs and Symptoms of Overexposure:

Inhalation: May cause a red, dry throat, coughing, excessive salivation, vomiting colic and diarrhea

Ingestion: No acute or chronic health effects recorded

Skin: May cause redness, itching, and burning

Eye: May cause redness, itching and watering

Health Hazards (Acute and Chronic):

Inhalation:

Acute: May cause irritation to the respiratory system, excessive salivation, vomiting, colic and diarrhea.

Chronic: No chronic health effects recorded

Ingestion:

No acute or chronic health effects recorded

Skin:

No acute or chronic health effects recorded

Eye:

Acute: Dusts and powder may cause irritation

Chronic: None chronic health effects recorded

Target Organs: None target organs recorded

Carcinogenicity: NTP? No IARC Monographs? No OSHA? No

Medical Conditions Aggravated by Exposure: Pre-existing respiratory disorders



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

Emergency and First Aid Procedures:

- Inhalation:* Remove victim to fresh air, keep warm and quiet, and give oxygen if breathing is difficult; seek medical attention
- Ingestion:* Give 1-2 glasses of milk or water and induce vomiting, seek medical attention. Never induce vomiting or give anything by mouth to an unconscious person
- Skin:* Remove contaminated clothing, brush material off skin, wash affected area with mild soap and water, and seek medical attention if symptoms persist
- Eye:* Flush eyes with lukewarm water, lifting upper and lower eyelids for at least 15 minutes and seek medical attention

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in case material is released or spilled:

Wear appropriate respiratory and protective equipment specified in section VIII. Isolate spill area, provide ventilation and extinguish sources of ignition. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for proper disposal. Take care not to raise dust.

Waste disposal method:

Dispose of in accordance with state, local, and federal regulations.

Hazard Label Information:

Store in cool, dry area and in tightly sealed container. Wash thoroughly after handling.

SECTION VIII - CONTROL MEASURES

Protective Equipment Summary (Hazard Label Information):

NIOSH approved respirator, impervious rubber gloves, safety glasses, clothes to prevent contact.

Ventilation:

Local Exhaust: To maintain concentration at low exposure levels.

Mechanical (General): Recommended.

Work/Hygienic/Maintenance Practices:

Implement engineering and work practice controls to reduce and maintain concentration of exposure at low levels. Use good housekeeping and sanitation practices. Do not use tobacco or food in work area. Wash thoroughly before eating or smoking. Do not blow dust off clothing or skin with compressed air.

Please be advised that N/A can either mean Not Applicable or No Data Has Been Established