



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

Chemtrec: (800) 424-9300
Poison Center: (800) 562-8236
Revision Date: January 8th, 2019

SAFETY DATA SHEET

Identity: Tantalum pentoxide

Formula: Ta₂O₅

SECTION I - GENERAL INFORMATION

Manufacturer: Super Conductor Materials, Inc.

The information below is believed to be accurate and represents the best information available to Super Conductor Materials, Inc. However, SCM makes no warranty, expressed or implied with respect to such information and assumes no liability resulting from its use.

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Molecular weight: 441.89

CAS #	OSHA PEL	ACGIH TLV	%
1314-61-0	5mg/m ³	5mg/m ³	0.0-100.0%

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

Physical States: Solid

Boiling Point: 1950°C

Melting Point: 1880°C

Evaporation Rate: N/A

Solubility in water: Insoluble/

Insoluble in alcohol, and mineral acids

Vapor Pressure (vs. air or mmHg): N/A

Density: 8.2 g/cm³ at 25°C

Flash Point: N/A

Appearance and odor: Beige powder and pieces, no odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Method Used: Non-Flammable


Explosive Limits: LEL: N/A

UEL: N/A

Extinguishing Media: Use suitable extinguishing agent for surrounding material and type of fire.

Special Fire Fighting Procedures: Firefighters must wear full face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. Fumes from fire are hazardous. Isolate runoff to prevent environmental pollution.

Unusual Fire and Explosion Hazards: When heated to decomposition, tantalum pentoxide may emit toxic fumes.



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

SECTION V - REACTIVITY DATA

Stability: Stable

Conditions to Avoid (instability): Raising dust

Incompatibility: N/A

Hazardous Decomposition or Byproducts: Tantalum oxide

Hazardous Polymerization: Will not occur

Conditions to avoid (hazardous polymerization): N/A

SECTION VI - HEALTH HAZARD DATA

Routes of entry: Inhalation? Yes Skin? No Eyes? No Ingestion? Yes Other? No

Signs and Symptoms of Overexposure: No data available

Health Hazards (Acute and Chronic):

Inhalation: Dusts can be mechanically irritating to lungs and upper respiratory tract.

Ingestion: May cause nausea, vomiting, dizziness, and/or diarrhea

Skin: May cause redness, itching and/or burning

Eye: Will cause irritation, redness, itching, watering and/or burning.

Target Organ: May affect the lungs

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

Medical Conditions Aggravated by Exposure: Pre-existing respiratory disorders.

Emergency and First Aid Procedures:

Inhalation: Remove victim to fresh air, keep warm and quiet, and give oxygen if breathing is difficult; seek medical attention

Ingestion: Give 1-2 glasses of milk or water and induce vomiting, seek medical attention. Never induce vomiting or give anything by mouth to an unconscious person.

Skin: Remove contaminated clothing, brush material off skin, wash affected area with mild soap and water, and seek medical attention symptoms persist.

Eye: Flush eyes with lukewarm water, lifting upper and lower eyelids for at least 15 minutes and seek medical attention immediately.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE


Steps to be taken in case material is released or spilled:

Wear appropriate respiratory and protective equipment specified in section VIII-Control Measures. Isolate spill area, provide ventilation. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for proper disposal. Take care not to raise dust.

USE NON-SPARKING TOOLS

Waste disposal method:

Dispose of in accordance with state, local, and federal regulations.



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

Hazard Label Information:

Store in cool, dry area and in tightly sealed container. Wash thoroughly after handling.

SECTION VIII - CONTROL MEASURES

Protective Equipment Summary (Hazard Label Information):

NIOSH approved respirator, impervious gloves, safety glasses, clothes to prevent contact, goggles or face shield.

Ventilation:

Local Exhaust: To maintain concentration at low exposure levels.

Mechanical (General): Recommended.

Work/Hygienic/Maintenance Practices:

Implement engineering and work practice controls to reduce and maintain concentration of exposure at low levels. Use good housekeeping and sanitation practices. Do not use tobacco or food in work area. Wash thoroughly before eating or smoking. Do not blow dust off clothing or skin with compressed air.

Please be advised that N/A can either mean Not Applicable or No Data Has Been Established