



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

Chemtrec: (800) 424-9300

Poison Center: (800) 562-8236

Revision Date: January 8th, 2019

SAFETY DATA SHEET

Identity: Tin Oxide

Formula: SnO

SECTION I - GENERAL INFORMATION

Manufacturer: Super Conductor Materials, Inc.

The information below is believed to be accurate and represents the best information available to Super Conductor Materials, Inc. However, SCM makes no warranty, expressed or implied with respect to such information and assumes no liability resulting from its use.

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Molecular weight: 134.69

CAS #	OSHA PEL	ACGIH TLV	%
21651-19-4	2 mg/m ³	2 mg (Sn)/m ³	0.0 – 100.0%

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

Physical States: Solid

Boiling Point: N/A

Vapor Pressure (vs. air or mmHg): N/A

Melting Point: 1080.00 °C (1976.0 °F)

Density: 6.45

Evaporation Rate: N/A

Flash Point: N/A

Solubility in water: Insoluble/

Insoluble in alcohol/ soluble in acids, concentrated NaOH and KOH solutions.

Appearance and odor: Brownish-black powder and pieces, no odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA:

Method Used: Unknown

Explosive Limits: LEL: N/A

UEL: N/A

Extinguishing Media: Use suitable extinguishing agent for surrounding material and type of fire

Special Fire Fighting Procedures:

Firefighters must wear full face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. Fumes from fire are hazardous. Isolate runoff to prevent environmental pollution.

Unusual Fire and Explosion Hazards:

–Tin oxide may emit toxic fumes if involved in a fire. Oxidation proceeds incandescently on heating at 300C in air.

–May ignite in nitrous oxide at 400C.



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

–May incandescence when heated in sulfur dioxide.

SECTION V - REACTIVITY DATA

Stability: Unstable

Conditions to Avoid (instability): May be unstable in air

Incompatibility: Strong acids and bases, non-metal oxides

Hazardous Decomposition or Byproducts: Tin and SnO₂

Hazardous Polymerization: Will not occur

Conditions to avoid (hazardous polymerization): None

SECTION VI - HEALTH HAZARD DATA

Routes of entry: Inhalation? Yes Skin? Yes Eyes? Yes Ingestion? Yes Other? No

Tin compounds have variable toxicity. Elemental tin and inorganic tin compounds have low toxicity and are poorly absorbed when ingested. Some inorganic tin salts are irritating or can liberate toxic fumes on decomposition. The latter is particularly true of tin halogens. (Sax, Dangerous Properties of Industrial Materials, eighth edition)

Signs and Symptoms of Overexposure:

Inhalation: May cause throat dryness, cough, headache, vomiting, chest pain, irritability, depression, loss of weight and pneumonitis.

Ingestion: No acute or chronic health effects recorded.

Skin: May cause redness and itching.

Eye: May cause redness, itching, burning sensation and watering.

Health Hazards (Acute and Chronic):

Inhalation:

Acute: Nuisance Dust. May cause irritation of the upper respiratory system.

Chronic: May cause pneumoconiosis.

Ingestion:

Acute: Poor absorption makes it relatively non-toxic.

Chronic: No chronic health effects recorded.

Skin:

Acute: May cause irritation.

Chronic: No chronic health effects recorded.

Eye:

Acute: May cause irritation.

Chronic: No chronic health effects recorded.

Target Organs: May affect the respiratory system.

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

Medical Conditions Aggravated by Exposure: Pre-existing respiratory disorders.



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

Emergency and First Aid Procedures:

- Inhalation:* Remove victim to fresh air, keep warm and quiet, and give oxygen if breathing is difficult; seek medical attention
- Ingestion:* Give 1-2 glasses of milk or water and induce vomiting, seek medical attention. Never induce vomiting or give anything by mouth to an unconscious person
- Skin:* Remove contaminated clothing, brush material off skin, wash affected area with mild soap and water, and seek medical attention if symptoms persist
- Eye:* Flush eyes with lukewarm water, lifting upper and lower eyelids for at least 15 minutes and seek medical attention

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in case material is released or spilled:

Wear appropriate respiratory and protective equipment specified in section VIII. Isolate spill area, provide ventilation and extinguish sources of ignition. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for proper disposal. Take care not to raise dust.

Waste disposal method:

Dispose of in accordance with state, local, and federal regulations.

Hazard Label Information:

Store in cool, dry area and in tightly sealed container. Wash thoroughly after handling.

SECTION VIII - CONTROL MEASURES

Protective Equipment Summary (Hazard Label Information):

NIOSH approved respirator, impervious gloves, safety glasses, clothes to prevent contact.

Ventilation:

Local Exhaust: To maintain concentration at low exposure levels.

Mechanical (General): Good general ventilation is recommended.

Work/Hygienic/Maintenance Practices:

Implement engineering and work practice controls to reduce and maintain concentration of exposure at low levels. Use good housekeeping and sanitation practices. Do not use tobacco or food in work area. Wash thoroughly before eating or smoking. Do not blow dust off clothing or skin with compressed air.

Please be advised that N/A can either mean Not Applicable or No Data Has Been Established