

Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · www.scm-inc.com Chemtrec: (800) 424-9300 Poison Center: (800) 562-8236 Revision Date: January 8th, 2019

SAFETY DATA SHEET

Identity: Titanium dioxide Formula: TiO2 SECTION I - GENERAL INFORMATION

Manufacturer: Super Conductor Materials, Inc.

The information below is believed to be accurate and represents the best information available to Super Conductor Materials, Inc. However, SCM makes no warranty, expressed or implied with respect to such information and assumes no liability resulting from its use.

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Molecular weight: 79.90

CAS #	OSHA PEL	ACGIH TLV	%
13463-67-7	15 mg/m3 total dust	10 mg/m3	0.0-100.0%

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

Physical States: Solid

Boiling Point: 368°C Melting Point: 1830.00°C - 1860.00°C Evaporation Rate: N/A Solubility in water: N/A Vapor Pressure (vs. air or mmHg): N/A Specific Gravity (Water=1): 3.9 Flash Point: N/A

Appearance and odor: White powder, no odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA:

Method Used: UnknownExplosive Limits: LEL: N/AUEL: N/AExtinguishing Media: Use suitable extinguishing agent for surrounding material and type of fire

Special Fire Fighting Procedures: Firefighters must wear full face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. Fumes from fire are hazardous. Isolate runoff to prevent environmental pollution.

Unusual Fire and Explosion Hazards: May have a violent or incandescent reaction with metals at high temperatures.

SECTION V - REACTIVITY DATA

Stability: Stable Conditions to Avoid (instability): None



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · www.scm-inc.com Incompatibility (Materials to avoid): Strong acids, aluminum, calcium, magnesium, potassium, sodium, zinc

Hazardous Decomposition or Byproducts: None recorded *Hazardous Polymerization:* Will not occur *Conditions to avoid (hazardous polymerization):* None

SECTION VI - HEALTH HAZARD DATA				
Routes of entry: Inhalation? Yes Ingest	tion? Yes Eyes? Yes	Skin? Yes	Other? No	

<u>Signs and Symptoms of Overexposure:</u> Inhalation: May cause a red, dry throat and coughing. Ingestion: No acute or chronic health effects recorded. Skin: May cause redness, burning, and itching.

Eye: May cause redness, burning, itching and watering.

Health Hazards (Acute and Chronic):

Inhalation:

Acute: Dust may cause irritation to the upper respiratory tract and mucous membranes. Chronic: May cause slight lesions in the lungs, lung fibrosis, bronchitis and emphysema.

Ingestion: Acute: No acute health effects recorded. Chronic: No chronic health effects recorded.

Skin: Acute: May cause skin irritation. Chronic: No chronic health effects recorded

Eye:

Acute: Prolonged or repeated contact may cause irritation. Chronic: No chronic health effects recorded.

Target Organs: No target Organs effects recorded

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No *Medical Conditions Aggravated by Exposure*: Pre-existing respiratory disorder

Emergency and First Aid Procedures:

Inhalation:	Remove victim to fresh air, keep warm and quiet, and give oxygen if breathing is difficult; seek medical attention
Ingestion:	Give 1-2 glasses of milk or water and induce vomiting, seek medical attention. Never induce vomiting or give anything by mouth to an unconscious person
Skin:	Remove contaminated clothing, brush material off skin, wash affected area with mild soap and water, and seek medical attention if symptoms persist
Eye:	Flush eyes with lukewarm water, lifting upper and lower eyelids for at least 15 minutes and seek medical attention



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · www.scm-inc.com

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in case material is released or spilled:

Wear appropriate respiratory and protective equipment specified in section VIII. Isolate spill area, provide ventilation and extinguish sources of ignition. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for proper disposal. Take care not to raise dust.

Waste disposal method:

Dispose of in accordance with state, local, and federal regulations.

Hazard Label Information:

Store in cool, dry area and in tightly sealed container. Wash thoroughly after handling.

SECTION VIII - CONTROL MEASURES

Protective Equipment Summary (Hazard Label Information):

NIOSH approved respirator, impervious gloves, safety glasses, clothes to prevent contact.

Ventilation:

Local Exhaust: To maintain concentration at or below the PEL, TLV Mechanical (General): Good general ventilation is recommended

Work/Hygienic/Maintenance Practices:

Implement engineering and work practice controls to reduce and maintain concentration of exposure at low levels. Use good housekeeping and sanitation practices. Do not use tobacco or food in work area. Wash thoroughly before eating or smoking. Do not blow dust off clothing or skin with compressed air.

Please be advised that N/A can either mean Not Applicable or No Data Has Been Established