



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

Chemtrec: (800) 424-9300
Poison Center: (800) 562-8236
Revision Date: January 8th, 2019

SAFETY DATA SHEET

Identity: Zirconium fluoride

Formula: ZrF₄

SECTION I - GENERAL INFORMATION

Manufacturer: Super Conductor Materials, Inc.

The information below is believed to be accurate and represents the best information available to Super Conductor Materials, Inc. However, SCM makes no warranty, expressed or implied with respect to such information and assumes no liability resulting from its use.

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Molecular weight: 167.21

CAS #	OSHA PEL	ACGIH TLV	%
7783-64-4	2.5mg (F)/m ³	2.5mg (F)/m ³	0.0-100.0%

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

Physical States: Solid

Boiling Point: N/A

Vapor Pressure (vs. air or mmHg): N/A

Melting Point: 600.00°C

Specific Gravity: 4.43 g/cm³

Evaporation Rate: N/A

Flash Point: N/A

Solubility in water: Soluble in cold/
decomposes in hot

Appearance and odor: White powder and pieces, no odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA:

Method Used: Non-flammable

Explosive Limits: LEL: N/A

UEL: N/A

Extinguishing Media: Use suitable extinguishing agent for surrounding material and type of fire

Special Fire Fighting Procedures:

Firefighters must wear full face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. Fumes from fire are hazardous. Isolate runoff to prevent environmental pollution.

Unusual Fire and Explosion Hazards:

–When heated to decomposition, zirconium fluoride may emit toxic fumes of fluorine.



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

–When exposed to high temperatures and in the presence of humid air, toxic and corrosive hydrogen fluoride fumes may be released.

SECTION V - REACTIVITY DATA

Stability: Unstable

Conditions to Avoid (stability): Protect from moisture and water

Incompatibility: None recorded

Hazardous Decomposition or Byproducts: Fumes of fluorine, hydrogen fluoride and zirconium oxide

Hazardous Polymerization: Will not occur

Conditions to avoid (hazardous polymerization): None

SECTION VI - HEALTH HAZARD DATA

Routes of entry: Inhalation? Yes Ingestion? Yes Eyes? Yes Skin? Yes Other? No

Zirconium compounds are not an important industrial poison. Most zirconium compounds in common use are insoluble and considered inert. Pulmonary granuloma in zirconium workers has been reported. (Sax, Dangerous Properties of Industrial Materials, eighth edition)

Inorganic fluorides are generally highly irritating and toxic. Chronic fluorine poisoning, or "fluorosis," occurs among miners of cryolite, and consists of sclerosis of the bones, caused by fixation of the calcium by fluorine. There may also be some calcification of the ligaments. The teeth are mottled, and there is osteosclerosis and ostemalacia. Large doses can cause very severe nausea, vomiting, and diarrhea, aggravate attacks of asthma and severe bone changes, making normal movements painful. Some signs of pulmonary fibrosis are noted. Some enzyme system effects are reported. Irritants to the eyes, skin and mucous membranes. Loss of weight, anorexia, anemia, wasting and cachexia and dental defects are among the common findings in chronic fluorine poisoning. There may be an eosinophilia and impairment of growth in young workers. Symptoms of intoxication include gastric, intestinal, circulatory, respiratory and nervous complaints and rashes. (Sax, Dangerous Properties of Industrial Materials, eighth edition)

Signs and Symptoms of Overexposure:

Inhalation: May cause ulcers of the upper respiratory tract, excessive salivation, vomiting, thirst, sweating, colic and diarrhea. Fibrosis may cause: sclerosis of the bones, calcification of ligaments, mottled teeth, osteosclerosis, and ostemalacia, loss of weight, anorexia, anemia, wasting, cachia and dental defects.

Ingestion: May cause nausea, vomiting, diarrhea, abdominal burning, cramp-like pain, as tiff spine, calcification of ligaments of the ribs and pelvis

Skin: May cause redness, itching and chemical burns

Eye: May cause redness, itching, watering and chemical burns

Health Hazards (Acute and Chronic):

Inhalation:

Acute: Severe irritant and corrosive to respiratory tract and mucous membranes.

Chronic: May cause fluorine poisoning, pulmonary edema and sever bone changes.

Ingestion:

Acute: Severe irritant and corrosive. May cause gastrointestinal irritation, nausea, and diarrhea

Chronic: May affect the circulatory, enzyme and nervous system.



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com

Skin:

Acute: May cause rashes and skin granulomas

Chronic: Severe irritant corrosive

Eye:

Acute: May cause irritation, watering, itching and/or swelling

Chronic: Severe irritant and corrosive

Target Organs: May affect skeleton, kidneys, central nervous system, respiratory system, eyes and skin

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

Medical Conditions Aggravated by Exposure: May cause or aggravate attacks of asthma

Emergency and First Aid Procedures:

Inhalation: Remove victim to fresh air, keep warm and quiet, and give oxygen if breathing is difficult; seek medical attention

Ingestion: Give 1-2 glasses of milk or water and induce vomiting, seek medical attention. Never induce vomiting or give anything by mouth to an unconscious person

Skin: Remove contaminated clothing, brush material off skin, wash affected area with mild soap and water, and seek medical attention if symptoms persist

Eye: Flush eyes with lukewarm water, lifting upper and lower eyelids for at least 15 minutes and seek medical attention

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in case material is released or spilled:

Wear appropriate respiratory and protective equipment specified in section VIII. Isolate spill area, provide ventilation and extinguish sources of ignition. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for proper disposal. Take care not to raise dust.

Waste disposal method:

Dispose of in accordance with state, local, and federal regulations.

Hazard Label Information:

Store in cool, dry area and in tightly sealed container. Wash thoroughly after handling.

SECTION VIII - CONTROL MEASURES

Protective Equipment Summary (Hazard Label Information):

NIOSH approved respirator, impervious butyl or rubber gloves, safety glasses, clothes to prevent contact.

Ventilation:

Local Exhaust: To maintain concentration at low exposure levels.

Special: Handle in a controlled environment

Mechanical (General): Not recommended.

Work/Hygienic/Maintenance Practices:



Super Conductor Materials, Inc.

391 Spook Rock Industrial Park, Suffern, NY 10901 · 845.368.0240 · Fax 845.368.0250 · www.scm-inc.com
Implement engineering and work practice controls to reduce and maintain concentration of exposure at low levels. Use good housekeeping and sanitation practices. Do not use tobacco or food in work area. Wash thoroughly before eating or smoking. Do not blow dust off clothing or skin with compressed air.

Please be advised that N/A can either mean Not Applicable or No Data Has Been Established
